

## RECC™ 3021 Chrome-Free Conversion Coating

### Product description

RECC™ 3021 is a patented, chrome-free, conversion coating for aluminum alloy surfaces. It provides corrosion protection and a surface for paint film adhesion.

- Free of chromates and other chromium compounds
- Single package, aqueous solution designed for spray application to aluminum alloy surfaces
- Used with RECC 1015 Chrome-free Deoxidizer

### Components



#### Mix ratio (by volume):

RECC 3021

Single component

### Specifications



RECC 3021 is listed on the following:

- F-15 Technical Order 1F-15A-23  
Rev 28

*Note: PPG Aerospace recommends you check the most recent specification QPLs for updated information.*

### Surface preparation and pretreatments



Refer to application guidelines section of this document.

### Instructions for use



#### Mixing instructions:

Single component. Stir before use.

*Note: It is important to condition the product for 24 hours prior to use by placing in the shop or hangar, with ambient temperatures between 13° and 35°C (55° to 95°F). The minimum temperature of the product should be 13°C (55°F) prior to using.*


# RECC™ 3021 Chrome-Free Conversion Coating

**Induction time:**

Not applicable

**Viscosity:** (23°C/73°F)

Not applicable.

**Pot life:**

Not applicable

## Application guidelines

**Optimum recommended application conditions:**

Temperature	15 - 30°C (59 - 86°F)
Relative Humidity	20 - 90%

**Application:**

- Clean and deoxidize the aluminum alloy surface with *RECC 1015*. Refer to the respective product information sheets.
- Adequately rinse surface using room temperature DI, RO, or Tap water.
- Apply *RECC 3021* in a well-ventilated area with adequate airflow.
- Spray apply *RECC 3021* to a break-free, clean and deoxidized surface (deoxidized using *RECC 1015*) until surface is adequately saturated.
- Keep surface saturated with *RECC 3021* for five minutes, reapplying as needed to keep treated surface wet.
- After application, do not rinse.
- Allow treated surface to air dry in a well-ventilated area with adequate airflow.
- Apply primer to the *RECC 3021* conversion coating treated surface following the appropriate dry-to-prime window.
- Apply topcoat to the primer following the appropriate dry-to-topcoat window.

*These application guidelines represent PPG's best advice in standard conditions. Some parameters will be influenced by environmental conditions, equipment settings, and other variables.*

**Equipment:**

*RECC 3021* can be applied with a plastic spray wand.

**Equipment cleaning:**

Clean equipment and tools with water.

# RECC™ 3021 Crome-Free Conversion Coating

## Physical Properties (product)



**Color** Clear



**Gloss** Not applicable



**Dry times:**

- Refer to application guidelines section of this document.



**VOC:**

RECC 3021

0 grams/liter



**Flash Point closed cup:**

RECC 3021

Not applicable

**Shelf Life:**

12 months from date of manufacture to most OEM material specifications. Consult the specification to verify shelf life requirements.

*Note: Shelf life is provided for original, unopened containers.*

*Note: The application and performance property values above are typical for the material, but not intended for use in specifications or for acceptance inspection criteria because of variations in testing methods, conditions and configurations.*

## Storage recommendations



Inspect the condition of the container to ensure compliance. The material should be stored at temperatures between 5°C to 35°C (41°F to 95°F) to ensure shelf life.

*Note: When procuring to a qualified material specification, follow those storage instructions.*

# RECC™ 3021 Crome-Free Conversion Coating

## Health precautions

This product is safe to use and apply when recommended precautions are followed. Before using this product, read and understand the Safety Data Sheet (SDS), which provides information on health, physical and environmental hazards, handling precautions and first aid recommendations. An SDS is available on request. Avoid overexposure. Obtain medical care in case of extreme overexposure.

**For industrial use only. Keep away from children.**

**Additional information can be found at: [www.ppgaerospace.com](http://www.ppgaerospace.com)**

**For sales and ordering information call the local PPG office at the numbers listed below:**

### **Asia Pacific**

#### **ASC – Australia**

Tel 61 (3) 9335 1557  
Fax 61 (3) 9335 3490

#### **ASC – Japan**

Tel 81 561 35 5200  
Fax 81 561 35 5201

#### **ASC – South East Asia**

Tel 65 6861 1119  
Fax 65 6861 6162

#### **ASC – Suzhou**

Tel (86-512) 6661 5858  
Fax (86-512) 6661 6868

#### **ASC – Tianjin**

Tel (86-022) 2482 8625  
Fax (86-022) 2482 8600

### **Europe and Middle East**

#### **ASC – Central Europe**

Tel 49 (40) 742 193 10  
Fax 49 (40) 742 139 69

#### **ASC – Middle East & India**

Tel (971) 4 883 9666  
Fax (971) 4 883 9665

#### **ASC – North Europe**

Tel 44 (0) 1388 770222  
Fax 44 (0) 1388 770288

#### **ASC – South Europe**

Tel 33 (0) 235 53 43 71  
Fax 33 (0) 235 53 54 44

### **Americas**

1 (818) 362-6711 or 1-800-AEROMIX

All recommendations, statements, and technical data contained herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and assumes all risks and liability resulting from his use of the product. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss, or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

*This document has been reviewed by the PPG Aerospace Export Control Department and has been determined to contain only EAR99 controlled data*

PRC-DeSoto International,  
Inc.

12780 San Fernando Road  
Sylmar, CA 91342

[www.ppgaerospace.com](http://www.ppgaerospace.com)

Issue Date: 07/21

Lit: 4473